

## Sash Cord Specification

*Traditional*

*Hardware*

**DIRECT**



### Waxed Cotton Sash Cord with Polyfilm Core

Traditional waxed cotton sash cord has improved strength and reduced stretch provided by the polypropylene film core. This is our classic cotton sash and is the benchmark in waxed sash cord that remains unequalled. The wax finish provides the weatherproofing and durability that this 16 plait construction is famous for. Waxing also provides efficient running on the pulleys for smooth window operation.

Diameter mm	Number	10m Hank Code No	100m Reel Code No	Breaking Load KG
5mm	3 (2c)	THD292	THD293	310
6mm	4 (3c)	THD280	THD281	340
7mm	5 (4c)	THD282	THD283	360
8mm	6 (5c)	THD284	THD285	390
10mm	8 (6c)	THD286	THD287	450



### 8 Plait Nylon Sash Cord

This 8 plait synthetic fibre sash cord has very high strength and shock resistance, is hard wearing, durable and resistant to mildew. This is a man – made fibre product at its best.

Diameter mm	Number	10m Hank Code No	100m Reel Code No	Breaking Load KG
6mm	4	THD288	THD289	520
8mm	6	THD290	THD291	1060

**UK Manufactured Sash Cord**



**Traditional Hardware Direct Ltd.,  
Unit 34, Darwen Enterprise Centre,  
Railway Road, Darwen,  
Lancashire BB3 3EH**

**Telephone No : 01254 773945 Fax No : 05601 120212**

**Email : [info@traditionalhardwaredirect.com](mailto:info@traditionalhardwaredirect.com)**